

SCHÜCO

ASE 60 Sliding Door

ROOMS
FLOODED
WITH LIGHT



Arkay Windows is a specialist large-scale fabricator with over 45 years of experience based in Watford, North West London.

Through growth built on putting our customers first, we have risen to supply some of the country's biggest retail companies, contractors and commercial installers.

 **Arkay Windows**



Watford: 01923 803923
London: 020 8889 6821

ase60@arkaywindows.com
arkaywindows.com

Schuco ASE 60 Sliding and Lift & Slide Door V1

 **Arkay Windows**



SCHÜCO

ASE 60 Sliding and Lift & Slide Door

The modular and scalable Schüco ASE 60 sliding and lift-and-slide system boasts excellent thermal insulation values, slimline face widths and comprehensive solutions in terms of design, openings and comfort.

Fittings allow for both Sliding and Lift & Slide options

Low Threshold - Concealable


Variable sightlines for a wide range of sizes and applications: 40mm to 112mm

Single, Double or Triple Track

Certified Burglar Resistance

Over 200 industry RAL colours - Single or Dual

Schüco SmartStop & SmartClose Compatible



Door Panel Size Limits

Maximum Width	3500mm
Maximum Height	3500mm
Maximum Weight	500KG

THRESHOLD HEIGHT	48 mm	
GLAZING THICKNESS	24 - 40 mm	
GLAZING METHOD	Beaded	
GLAZING	Double or Triple	
BURGLAR RESISTANCE	RC 2, DIN V ENV 1627	
SIGHTLINE (SLIM)	40 mm	
SIGHTLINE (STANDARD)	102 mm	
SIGHTLINE (HEAVY DUTY)	112 mm	
FRAME DEPTH	2 RAIL	140 mm
FRAME DEPTH	3 RAIL	220 mm

SCHÜCO

ASE 60 Sliding and Lift & Slide Door

Add a personal touch to the sliding doors.

Colours:

Choose from over 200 industry RAL colours. Select different colours outside and inside for the frame (dual frame colour). The polyester powdercoat paint is baked onto the aluminium to create a high quality, durable and tough finish to withstands the rigors of UK weather.

Finishes:

Choose from a wide range of surface treatments and anodised finishes (matt, gloss, semi gloss, anodised, textured) Subject to availability.

Handles Colours: Subject to availability.

- RAL 9005 Black
- RAL 9010 Pure White
- RAL 9016 Traffic White
- CO Silver Anodised

Handle Types:

- Handle with inside cylinder. Pull grip on the outside.
- Handle without inside cylinder. Pull grip on the outside.
- Handle with cylinder on both sides.

Glass Type Examples:

Low emission (standard), safety & security (toughened laminated), solar control, self-cleaning, acoustic, decorative, coloured.

PERFORMANCE	
U-VALUE	From 1.1 W/m ² K
AIR PERMEABILITY	Class 4, EN 12207
WATER TIGHTNESS	Class E 900, EN 12208
WIND RESISTANCE	Class C5/B5